



TEST REPORT

Reference No. : WTD23D12265582W004
FCC ID : 2ARWCCVZ-0303
Applicant : Coolr Group Inc
Address : 4451 Brookfield Corporate Dr Suite 111, Chantilly, VA 20151, US
Manufacturer 1 : Suga Electronics (Dongguan) Co.,Ltd.
Address : Suga High-tech Industrial Park, No.8 Fulong Road, Sanzhong village, Qingxi Town, Dongguan City, Guangdong Province, China
Manufacturer 2 : Suga International (Vietnam) Company Limited
Address : Lo so CN11-3, Que Vo 3 Industrial Park, Que Tan Commune, Que Vo District, Bac Ninh Province, Vietnam
Product : VistaZ
Model(s) : CVZ-0303
Standards : FCC 47CFR Part 2 Subpart J Section 2.1091
Date of Receipt sample : 2023-12-14
Date of Test : 2024-01-02 to 2024-01-09
Date of Issue : 2024-01-18
Test Result : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Testing Group Co., Ltd.

Address: No. 77, Houjie Section, Guantai Road, Houjie Town, Dongguan City, Guangdong, China

Tel: +86-769-2267 6998

Fax: +86-769-2267 6828

Compiled by:

Approved by:

James Cheng / Project Engineer

Deval Qin / Designated Reviewer



2. Contents

	Page
1. COVER PAGE.....	1
2. CONTENTS.....	2
3. REVISION HISTORY.....	3
4. GENERAL INFORMATION.....	4
4.1. GENERAL DESCRIPTION OF E.U.T.	4
4.2. DETAILS OF E.U.T.	4
4.3. TEST FACILITY.....	5
4.4. SUBCONTRACTED	5
4.5. ABNORMALITIES FROM STANDARD CONDITIONS.....	5
5. TEST SUMMARY.....	6
6. RF EXPOSURE.....	7
6.1. REQUIREMENTS.....	7
6.2. THE PROCEDURES / LIMIT	7
6.3. MPE CALCULATION METHOD.....	8
6.4. RADIO FREQUENCY RADIATION EXPOSURE EVALUATION.....	8

WALTEK



3. Revision History

Test Report No.	Date of Receipt sample	Date of Test	Date of Issue	Purpose	Comment	Approved
WTD23D12265582W004	2023-12-14	2024-01-02 to 2024-01-09	2024-01-18	Original	-	Valid

WALTEK



4. General Information

4.1. General Description of E.U.T.

Product:	VistaZ
Model(s):	CVZ-0303
Model Description:	N/A
BT Version:	V5.4
Wi-Fi Specification:	802.11b/g/n HT20
Hardware Version:	V01 Rev 0.02
Software Version:	v17.1

4.2. Details of E.U.T.

Operation Frequency:	BLE: 2402-2480MHz 2.4G Wi-Fi: 802.11b/g/n HT20: 2412~2462MHz
Max. RF output power:	BLE: -4.18dBm 2.4G Wi-Fi: 13.10dBm
Modulation Technology:	BLE: GFSK 2.4G Wi-Fi: DSSS, OFDM
Antenna installation:	ceramic antenna
Antenna Gain:	BLE: 2.0dBi 2.4G Wi-Fi: 3.77dBi

Note:

#: The antenna gain is provided by the applicant, and the applicant should be responsible for its authenticity, WALTEK lab has not verified the authenticity of its information.

Ratings: DC 3.7V by battery

Battery: DC 3.7V, 2500mAh, 9.25Wh



4.3. Test Facility

The test facility has a test site registered with the following organizations:

ISED CAB identifier: CN0013. Test Firm Registration No.: 7760A.

Waltek Testing Group Co., Ltd. Has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files.

Registration number 7760A, October 15, 2016.

FCC Designation No.: CN1201. Test Firm Registration No.: 523476.

Waltek Testing Group Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration number 523476, September 10, 2019.

4.4. Subcontracted

Whether parts of tests for the product have been subcontracted to other labs:

☐ Yes ☒ No

If Yes, list the related test items and lab information:

Test Lab: N/A

Lab address: N/A

Test items: N/A

4.5. Abnormalities from Standard Conditions

None.



5. Test Summary

Test Items	Test Requirement	Result
Maximum Permissible Exposure (Exposure of Humans to RF Fields)	FCC Part 2.1091	PASS

WALTEK



6. RF Exposure

Test Requirement: FCC 47CFR Part 2 Subpart J Section 2.1091

Evaluation Method: FCC 47CFR Part 1 Subpart I Section 1.1310,
KDB 447498 D01 General RF Exposure Guidance v06

6.1. Requirements

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2 m normally can be maintained between the user and the device.

6.2. The procedures / limit

Table 1 to § 1.1310(e)(1) - Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm ²)	Averaging time (minutes)
(i) Limits for Occupational/Controlled Exposure				
0.3-3.0	614	1.63	*(100)	≤6
3.0-30	1842/f	4.89/f	*(900/f ²)	<6
30-300	61.4	0.163	1	<6
300-1,500			f/300	<6
1,500-100,000			5	<6
(ii) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	<30
1.34-30	824/f	2.19/f	*(180/f ²)	<30
30-300	27.5	0.073	0.2	<30
300-1,500			f/1500	<30
1,500-100,000			1	<30

f = frequency in MHz. * = Plane-wave equivalent power density.



6.3. MPE Calculation Method

$$S = \frac{P \times G}{4 \times \pi \times R^2}$$

S = power density (in appropriate units, e.g. mW/cm²)

P = output power to the antenna (in appropriate units, e.g., mW).

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain.

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

From the peak EUT RF output power, the minimum mobile separation distance, R=20cm, as well as the gain of the used antenna, the RF power density can be obtained

6.4. Radio Frequency Radiation Exposure Evaluation

Band	Antenna Gain (dBi)	Antenna Gain (numeric)	Max. Peak Output Power (dBm)	Peak Output Power (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)
BLE	2.00	1.58	-4.18	0.38	0.000120	1.0
2.4G Wi-Fi	3.77	2.38	13.10	20.42	0.009676	1.0
GSM	0.55	1.14	32.20	1659.59	0.374691	0.566
LTE	1.90	1.55	20.51	112.46	0.034648	1.0

Note:

1. For conservativeness, the lowest frequency of each band is used to determine the MPE limit of that band.
2. Chose the maximum power to do MPE analysis.
3. GSM and LTE power is FCC ID:XMR201910BG95M3

Consider the BLE and wifi can transmitting simultaneously, the total transmitting MPE rate as below formula:

MPE rate=Power density of BLE/limit + Power density of wifi/limit <1

Evaluation mode	Power density/limit	Sum of the MPE rate	limit
BLE	0.000120	0.009796	1.0
2.4G WIFI	0.009676		

Consider the BLE and GSM or LTE can transmitting simultaneously, the total transmitting MPE rate as below formula:

MPE rate=Power density of BLE/limit + Power density of GSM/limit <1

Evaluation mode	Power density/limit	Sum of the MPE rate	limit
BLE	0.000120	0.66212	1.0
GSM	0.374691		



MPE rate=Power density of BLE/limit + Power density of LTE/limit <1

Evaluation mode	Power density/limit	Sum of the MPE rate	limit
BLE	0.000120	0.034768	1.0
LTE	0.034648		

Conclusion:

RF Exposure is FCC compliant.

=====End of Report=====

WALTEK